

#15 FELT HAS GONE TO THE DOGS.



Home owners and builders are **barking** for new synthetic underlayments... even though they only have a budget for #15 felt.

Bite back with **Shingle Dog 15™**, the price-competitive #15 felt replacement.

ASTM D226/D4869 • FL 10078 • CAN/CSA A123.3-05

TOUGHER

Unlike #15 felt that tears and rips easily under foot or high wind, **SHINGLE DOG 15™** will withstand much tougher installation conditions. **SHINGLE DOG 15™** is 25X stronger than #15 felt. Now that's junkyard dog tough!

LIGHTER

One roll of **SHINGLE DOG 15™** covers 10 squares and weighs only 20 lbs., that's 6X lighter than #15 felt. One roll of **SHINGLE DOG 15™** covers 1000 square feet. Use fewer rolls, use less truck space, lift and carry a lot less weight on every job.

SMARTER

Upgrade from #15 felt, and forget about tearing, ripping, wrinkling, water absorption, blow offs, hot oily surfaces, and long term dry-out & cracking that plagues #15 felt. Wider rolls, fewer rolls, more coverage per lap, faster installation vs. #15 felt. Get a cooler grey surface, and synthetic construction impervious to mold growth. Now that's smart!

CALL TODAY AND GET STARTED WITH **SHINGLE DOG 15™**

855.602.2095

TECHNICAL DATA

PROPERTY ¹	STANDARD	SHINGLE DOG 15-S™	#15 FELT
Permeability	ASTM E96	0.05 Perms	5 Perms
H ₂ O Transmission	ASTM D4869	Pass	Pass
Tensile Strength	ASTM D751	81 (37 kg)	54 (25 kg)
Tear Strength	ASTM D2523	30 lbs (13.5 kg)	0.9 lbs (0.4 kg)
Burst Strength	ASTM D751	170 psi (1180 kPa)	35 psi (242 kPa)
Elongation	ASTM D751	20%	3%
Water Absorption	ASTM D1970	0%	35%
Moisture Buckling	-	0" (0 mm)	0.5" (12.5mm)
Weight per Square	ASTM D5261	2 lbs (0.9 kg)	12.5 lbs (5.7 kg)
Nominal Thickness	ASTM D1777	7 mils (0.18 mm)	21 mils (0.53mm)
Temperature Range	-	-70°F to 300°F (-55°C to 150°C)	14°F to 212°F (-10°C to 100°C)
Length per Roll		250 ft (76.2 m)	144 ft (43.9 m)
Width per Roll		48" (1.05 m)	36" (0.91m)
Weight per Roll		20 lbs (9 kg)	53 lbs (24 kg)
Roll Coverage ²		10 sq (92.9 m ²)	4.3 sq (40 m ²)
Rolls/Pallet		64	30
Pallet Weight		1380 lbs (627 kg)	1640 lbs (745 kg)

1. Values, weights, and measures are typical data and not limiting specifications. All values +/- 10%
2. Nominal

THE #15 FELT REPLACEMENT • FOR USE UNDER ASPHALT SHINGLES • 15 YEAR WARRANTY

SHINGLE DOG 15[™] SYNTHETIC UNDERLAYMENT S